

DURA-ABS™

AUTO-BATCH SYSTEM PRODUCT SPECIFICATIONS



Operating Temp	-10°F to 130°F
Flow Rate	Up to 15 GPM
Meter Accuracy	+/- .5%
Backlit LCD Display	Yes; with back-light timeout
Max Pressure	40 psi
Pump Ports	In: 1" FNPT x 2" MNPT; Out: 1" FNPT
Units Measured	Gallons / Liters / Ounces
Chemically Resistant	Yes, EPDM or Viton® seals
Calibration	Preset, Quick List or Manual
Mounting Range	Fixed or In-line
Vibration / Shock Resistant	Yes
EPA Compliant	Yes, 165.45

- / Intuitive interface allows for the selection of manual or automatic operation with the flip of a switch
- / High-flow pump with up to 15GPM flow rate
- / Optimized for repeatable batching; returns to the last volume amount dispensed
- / 100% moisture sealed circuitry
- / Includes Dura-Meter™ with impact resistant Lexan™ faceplate
- / Available in 12 Volt or 110 Volt, and EPDM or Viton® options
- / Features a 2 year warranty

How It Works

- 1 Select the volume desired
- 2 Press START
- 3 The pump will begin to dispense fluid and automatically shuts off when complete.

DPABS-4312E EPDM 12 Volt	DPABS-4312V Viton® 12 Volt
DPABS-4315E EPDM 110 Volt	DPABS-4315V Viton® 110 Volt



DURA PRODUCTS
Technology with Lasting Value

www.DuraProducts.com
Arcadia, IN 46030 | 855-502-3872

©2015 Dura Products, Inc.

NEW FOR 2017!

*The industry's ONLY transfer system offering
an automated dispensing option*

DURA-ABS™ AUTO-BATCH SYSTEM



- / Intuitive interface allows for the selection of manual or automatic operation with the flip of a switch
- / High-flow pump with up to 15GPM flow rate
- / Optimized for repeatable batching; returns to the last volume amount dispensed
- / 100% moisture sealed circuitry
- / Includes Dura-Meter™ with impact resistant Lexan™ faceplate
- / Available in 12 Volt or 110 Volt, and EPDM or Viton® options
- / Features a 2 year warranty

How It Works

- 1 Select the volume desired
- 2 Press START
- 3 The pump will begin to dispense fluid and automatically shuts off when complete.

