

# DURA-METER™

## PRODUCT SPECIFICATIONS



*Customer should always check calibration before use*

<b>Operating Temp</b>	-10°F to 130°F
<b>Flow Rate</b>	2 to 22 GPM
<b>Meter Accuracy</b>	+/- .5%
<b>Backlit LCD Display</b>	Yes; with back-light timeout
<b>Max Pressure</b>	40 psi
<b>Power Source</b>	4 "AAA" batteries; strength indicator
<b>Nutating Disc</b>	Yes
<b>Wetted Materials</b>	Polypropylene; 304 Stainless Steel; Ryton; EPDM or Viton® Seals
<b>Housing Chamber</b>	Polypropylene
<b>Moisture Sealed Construction</b>	Yes; with sealed circuitry
<b>Ports</b>	In: 1" FNPT x 2" MNPT; Out: 1" FNPT
<b>Meter Reset Feature</b>	Yes
<b>Liquid Flash-point</b>	100°F / 37.8° C
<b>Total Fluid Count</b>	Yes
<b>Amount Metered</b>	Yes
<b>Batch Count</b>	Yes
<b>Units Measured</b>	English or Metric; GPM or LPM
<b>Control Panel</b>	4 buttons
<b>Chemically Resistant</b>	Yes
<b>Calibration Units</b>	Gallons / Liters
<b>Calibration</b>	Preset, Quick List or Manual
<b>Mounting Range</b>	Fixed or In-line
<b>Vibration / Shock Resistant</b>	Yes
<b>Info / Help Screen</b>	Yes
<b>Dimensions</b>	5-1/4" W x 5-1/4" H x 4-1/4" D
<b>Weight</b>	1.5 lbs
<b>EPA Compliant</b>	Yes

- / Made of impact resistant Lexan™ faceplate
- / 100% moisture-sealed circuitry makes meter impervious to water intrusion
- / Menu driven backlit display
- / Plumbed both for in-line and 90 degree applications
- / Supported by a Quick List reference chart
- / Extended battery life with use of 4 "AAA" batteries
- / Faceplate over-molded with santoprene and filled with gel for improved shock resistance
- / Features 2 Year Service Warranty Plan
- / Includes 2 Year Maintenance Program

**DP-3000E** EPDM

**DP-3000V** Viton®

*Must specify EPDM (product # and E) or Viton® (product # and V) when ordering.*



**DURA PRODUCTS**

Technology with Lasting Value

[www.DuraProducts.com](http://www.DuraProducts.com)

Arcadia, IN 46030 | 855-502-3872

©2015 Dura Products, Inc.