

DURA-PUMP™ DEF

PRODUCT SPECIFICATIONS



Check Valve	Internal; EPA 165.45 compliant
Vertical Suction Lift	Self-priming to 10ft
Power Cord	12 Volt:20ft; 110 Volt: 6.5ft
Pump Type	Self-priming, Positive Displacement Diaphragm pump
Motor	1/4 HP
Amps	12 Volt:18.5; 110 Volt: 2.0
Suction Port	2" Male and 1" Female NPT thread
Discharge Port	1" Female NPT thread
Temperature	Max: 130 degree; Min: -15 degrees
Flow Rate	Max: 10GPM
Discharge Pressure	Max: 22psi
Motor Enclosure	Sealed; EPDM
Run-Dry Capability	Yes
Run Time	30 Minute Duty Cycle
Thermal Overload Protection	Yes
Upper Housing	Polypropylene
Bottom Housing	Polypropylene
Chemically Resistant	Yes
Fluid	Non-flammable
Construction Material	Polypropylene; 304 Stainless Steel
Wetted Material	Polypropylene; Santoprene (Shore 73); 304 Stainless Steel; EPDM Seals
Cartridge	Polyphenylene Sulfide
Diaphragm	1; Santoprene
O-Ring	EPDM
Valves	Stainless Steel
Bung Adapter Size	2" NPT
Weight	14 lbs
Length	12 Volt: 14-1/4"; 110 Volt: 15-1/2"
Auto-Shut Off	Yes; optional for 110 Volt
ISO22241-3 Compliant	Yes

/ High-Flow pump with up to 15GPM free flow rate and 10+GPM with 3/4" discharge hose and nozzle

/ Self-priming diaphragm pump with internal bypass

/ Motor thermally protected from overheating
/ 30 minute duty cycle

/ Suction ports has 2" Male NPT and 1" Female NPT

/ Pump is easily field serviceable

/ 10 minute shut-off option available (110V only)

/ Features 2 Year Service Warranty plan

/ Includes 2 Year Maintenance Program

DEF-2012E 12 volt

DEF-2015E 110 volt



DURA PRODUCTS
Technology with Lasting Value

www.DuraProducts.com
Arcadia, IN 46030 | 855-502-3872

©2015 Dura Products, Inc.