

DURA-PUMP™

PRODUCT SPECIFICATIONS



Check Valve	Internal; EPA 165.45 compliant
Vertical Suction Lift	Self-priming to 10ft
Power Cord	12 Volt: 12ft; 110 Volt: 6.5ft
Pump Type	Self-priming, Positive Displacement Diaphragm pump
Motor	1/4 HP
Amps	12 Volt: 18.5; 110 Volt: 2.0
Suction Port	2" Male and 1" Female NPT thread
Discharge Port	1" Female NPT thread
Temperature	Max: 130 degree; Min: -15 degrees
Flow Rate	Max: 15GPM
Discharge Pressure	Max: 22psi
Motor Enclosure	Sealed; EPDM/Viton®
Run-Dry Capability	Yes
Run Time	30 Minute Duty Cycle
Thermal Overload Protection	Yes
Upper Housing	Polypropylene
Bottom Housing	Polypropylene
Chemically Resistant	Yes
Fluid	Non-flammable
Construction Material	Polypropylene; 304 Stainless Steel
Wetted Material	Polypropylene; 304 Stainless Steel; Santoprene (Shore 73); EPDM or Viton® Seals
Cartridge	Polyphenylene Sulfide
Diaphragm	1; Santoprene
O-Ring	EPDM or Viton®
Valves	Stainless Steel
Bung Adapter Size	2" NPT
Weight	14 lbs
Length	12 Volt: 14-1/4"; 110 Volt: 15-1/2"

- / High-Flow with up to 15GPM free-flow rate
- / Self-priming diaphragm pump with internal by-pass
- / Motor thermally protected from overheating
- / 30 minute duty cycle
- / Suction ports has 2" Male NPT and 1" Female NPT
- / Pump is easily field serviceable
- / Features 2 Year Service Warranty Plan
- / Includes 2 Year Maintenance Program

DP-4012 12 volt

DP-4015 110 volt

(Available in EPDM or Viton®)

Must specify EPDM (**product # and E**) or Viton® (**product # and V**) when ordering.



DURA PRODUCTS
Technology with Lasting Value

www.DuraProducts.com

Arcadia, IN 46030 | 855-502-3872

©2015 Dura Products, Inc.