

DURA-METER™



The meter will turn **ON** with any button press or when fluid passes through the meter. It will turn **OFF** when not in use.

Use buttons to navigate the four main menus; **Reset, Program, Calibration, Info.** The buttons correspond to the on screen indicators.



4-AAA batteries provide about 70 hours of use with the backlight turned **ON**, and about 300 hours with the backlight **OFF**.


Operating Temp	-10°F to 130°F, -23°C to 54°C
Flow Rate	2 to 22GPM, 7.5 to 83LPM
Meter Accuracy	+/- .5%
Backlit LCD Display	Yes; with back-light timeout
Max Pressure	40 PSI
Power Source	4 "AAA" batteries; strength indicator
Nutating Disc	Yes
Wetted Materials	Polypropylene; 304 Stainless Steel; Ryton; EPDM, Viton® or Silicone seals
Housing Chamber	Polypropylene
Moisture Sealed	Yes; with sealed circuitry
Amount Metered	Yes
Batch Count	Yes
Units Measured	Gallons, Liters and Ounces
Chemically Resistant	Yes
Calibration	Quick List or Manual
Dimensions	5-1/4" W x 5-1/4" H x 4-1/4" D
Weight	1.5 lbs
EPA Compliant	Yes

TECHNICAL SPECIFICATIONS

CALIBRATION

NOTE: Use a primed system. Verify your calibration. Fluid viscosity changes with temperature.

QUICK LIST



Select a thickness number. For most agricultural chemicals, 8 is a good starting point.


Check

Pump 5 Gallons and see how close you are


Adjust

Each reference number represents 1% change. If the meter reads high, lower the number. (meter shows 5.25 gallons, adjust the number down 5% or 5 numbers.)

Repeat as needed




MANUAL



Once the cal jug has 5 gallons in it, Press "Cont"inue button

Adjust "Up" or "Down" to match the volume in the Cal Jug



METHOD TRAITS

QUICK LIST

- Number is the same across any Dura-Meter, great for fleet use

MANUAL

- Most accurate
- Usually only takes one attempt
- Adjustable to compensate for different measurement containers; 2.5-7 Gallon range



DURA PRODUCTS
Technology with Lasting Value
www.DuraProducts.com
Arcadia, IN 46030 | (855) 502-3872

DURA-ABS™

AUTO-BATCH SYSTEM



A check valve has been included to keep the system primed. **Accuracy depends on the system staying primed.**

Operating Temp	-10°F to 130°F, -23°C to 54°C
Flow Rate	2 to 22GPM, 7.5 to 83LPM
Meter Accuracy	+/- .5%
Backlit LCD Display	Yes; with back-light timeout
Max Pressure	40 PSI
Power Source	4 "AAA" batteries; strength indicator
Nutating Disc	Yes
Wetted Materials	Polypropylene; 304 Stainless Steel; Ryton; EPDM, Viton® or Silicone seals
Housing Chamber	Polypropylene
Moisture Sealed	Yes; with sealed circuitry
Amount Metered	Yes
Batch Count	Yes
Units Measured	Gallons, Liters and Ounces
Chemically Resistant	Yes
Calibration	Quick List or Manual
Dimensions	5-1/4" W x 5-1/4" H x 4-1/4" D
Weight	1.5 lbs
EPA Compliant	Yes


TECHNICAL SPECIFICATIONS

5 SAVED CALIBRATIONS

This meter is equipped with the ability to save and recall five different manual calibrations. Always be aware of the cal factor or Fluid # being used and **VERIFY!**

SAVING:

Manually calibrate. After pressing "Cont", you will be prompted to enter the fluid # where you want the calibration stored.



RECALLING:

Hold down the "Cal" button. Select "PreCal" and then the Fluid #.



NOTE: Use a primed system. Always verify your calibration. Fluid viscosity changes with temperature.

AUTO-BATCH OPERATION



- 1 Set Amount
- 2 Press start
- 3 The pump will begin to dispense fluid and automatically shuts off when complete.


NOTE: The calibration setting that is used in Auto mode, is the last calibration the meter was assigned.

PUMP SWITCH OPERATION



Pump switch must be in the ON position for Auto mode to work. Before switching to manual mode, place the pump switch in the OFF position. **Failure to do so, can result in unwanted product being dispensed.**

VOLUME ADJUSTMENT



Use "Up" or "Down" buttons to change amount. Scroll speed increases the longer you hold the buttons. "Reset" defaults to 10Gal, 40L, & 128Oz.