

# DURA-METER™ DEF

## PRODUCT SPECIFICATIONS



<b>Operating Temp</b>	-10°F to 130°F, -23°C to 54°C
<b>Flow Rate</b>	2 to 20 GPM, 7.5 to 75.7 LPM
<b>Meter Accuracy</b>	+/- .5%
<b>Backlit LCD Display</b>	Yes; with back-light timeout
<b>Max Pressure</b>	40 psi
<b>Power Source</b>	2 "AAA" batteries; strength indicator
<b>Body Material</b>	Polypropylene; EPDM Seals
<b>Nutating Disc</b>	Yes
<b>Wetted Materials</b>	Polypropylene; 304 Stainless Steel
<b>Housing Chamber</b>	Polypropylene
<b>Moisture Sealed Construction</b>	Yes
<b>Ports</b>	In: 1" FNPT x 2" MNPT; Out: 1" FNPT
<b>Meter Reset Feature</b>	Yes
<b>Liquid Flash-point</b>	100°F / 37.8° C
<b>Total Fluid Count</b>	Yes
<b>Amount Metered</b>	Yes
<b>Batch Count</b>	Yes
<b>Units Measured</b>	English or Metric; GPM or LPM
<b>Control Panel</b>	4 buttons
<b>Chemically Resistant</b>	No
<b>Calibration Units</b>	Gallons / Liters
<b>Calibration</b>	Preset or Manual
<b>Mounting Range</b>	Fixed or In-line
<b>Vibration / Shock Resistant</b>	Yes
<b>Info / Help Screen</b>	Yes
<b>Dimensions</b>	5-1/4" W x 5-1/4" H x 4-1/4" D
<b>Weight</b>	1.5 lbs
<b>ISO22241-3 Compliant</b>	Yes

- 100% Moisture-sealed circuitry makes meter impervious to water intrusion
- Meter calibrated for DEF
- Same great menu driven backlit display
- Plumbed for both in-line and 90° applications
- Features 2 Year Service Warranty plan
- Includes 2 Year Maintenance Program

### DP-3000D



**DURA PRODUCTS**

Technology with Lasting Value

[www.DuraProducts.com](http://www.DuraProducts.com)

Arcadia, IN 46030 | (317) 984-4003

©2024 Dura Products, Inc.