

DURA PRODUCTS

2" HIGH-FLOW DURA-METER™



- Intuitive menu-driven backlit display
- Impact resistant Lexan™ faceplate
- 100% Moisture-sealed circuitry
- 2" Manifold flanged meter body
- Multiple plumbing options
- Includes a 2-year Warranty & Maintenance Program

SPECIFICATIONS	
Nominal Size	2"
Model	Dura HFM 2
Batteries	(2) 9 Volt
Accuracy	+ / - 0.5%
Backlit Display	Yes
GPM	40 - 300
Wetted Materials	GF Polypropyl, Viton®, EPDM or Silicone seal, Sapphire

ORDERING INFORMATION		
DP-HFM2V Viton®	DP-HFM2E EPDM	DP-HFM2S Silicone



Moisture sealed circuitry.



Special Features

- Easily serviced
- Extended battery life with use of (2) 9V batteries
- Fluid flow initiates measurement
- Versatile plumbing configurations
- Displays batch and total volume
- Gallons / Liters flow rate measurement



DURA PRODUCTS
Technology with Lasting Value
www.DuraProducts.com
Arcadia, IN 46030 | (317) 984-4003

2" HIGH-FLOW DURA-METER™



SPECIFICATIONS	
Nominal Size	2"
Model	DP-HFM2
Connection	M220 flange
Meter Accuracy	+/- 0.5%
Non-conductive Fluids	Yes
Fluid Flow Initiates Measurement	Yes
Batteries	(2) 9 Volt
Battery Life Indicator	Yes
Backlit Display	Yes
Minimum GPM	40
Maximum GPM	300
Minimum Temp	+ 32 °F
Maximum Temp	+ 140 °F
Battery Size/Voltage	9V
Meter Type/Style	Paddlewheel
Body Construction Material	GF Polypropylene
Paddle Bearing Construction Material	Sapphire

* With manual calibration



DURA PRODUCTS
Technology with Lasting Value
www.DuraProducts.com
Arcadia, IN 46030 | (317) 984-4003