

DURA-METER™ DEF

PRODUCT SPECIFICATIONS



Operating Temp	-10°F to 130°F, -23°C to 54°C
Flow Rate	2 to 20 GPM, 7.5 to 75.7 LPM
Meter Accuracy	+/- .5%
Backlit LCD Display	Yes; with back-light timeout
Max Pressure	40 psi
Power Source	2 "AAA" batteries; strength indicator
Body Material	Polypropylene; EPDM Seals
Nutating Disc	Yes
Wetted Materials	Polypropylene; 304 Stainless Steel
Housing Chamber	Polypropylene
Moisture Sealed Construction	Yes
Ports	In: 1" FNPT x 2" MNPT; Out: 1" FNPT
Meter Reset Feature	Yes
Liquid Flash-point	100°F / 37.8° C
Total Fluid Count	Yes
Amount Metered	Yes
Batch Count	Yes
Units Measured	English or Metric; GPM or LPM
Control Panel	4 buttons
Chemically Resistant	No
Calibration Units	Gallons / Liters
Calibration	Preset or Manual
Mounting Range	Fixed or In-line
Vibration / Shock Resistant	Yes
Info / Help Screen	Yes
Dimensions	5-1/4" W x 5-1/4" H x 4-1/4" D
Weight	1.5 lbs
ISO22241-3 Compliant	Yes

- 100% Moisture-sealed circuitry makes meter impervious to water intrusion
- Meter calibrated for DEF
- Same great menu driven backlit display
- Plumbed for both in-line and 90° applications
- Features 2 Year Service Warranty plan
- Includes 2 Year Maintenance Program

DP-3000D



DURA PRODUCTS

Technology with Lasting Value

www.DuraProducts.com

Arcadia, IN 46030 | (317) 984-4003

©2024 Dura Products, Inc.