DURA PRODUCTS

INTRODUCING OUR NEW 2" AND 3" DURA AUTO-BATCH™ HIGH-FLOW METER

Fast. Simple. Safe.™



| ORDERING INFORMATION | | | |
|----------------------|-------------------------|-----------------------|--|
| 2" | DPAB-HFM2KITV Viton® | DPAB-HFM2KITE EPDM | |
| 3" | DPAB-HFM3KITV Viton® | DPAB-HFM3KITE EPDM | |

| KIT CONTAINS | | | |
|-----------------------------------|--|--|--|
| Valves | Custom Pressure Relief & Electric Valve | | |
| Meter Auto-Batch™ High-Flow Meter | | | |
| Other | All hose clamps, gaskets, reducer couplings & tees | | |



Moisture sealed circuitry.



NOW with ₿Bluetooth® wireless connectivity! Control it with the Dura Remote App. Compatible with Android™ or Apple® phones or tablets.





The Dura Auto-Batch™ High-Flow Meter is an automated device for transferring fluids. You just enter the amount you want, turn on the pump, and press Start. The meter opens a valve to send the fluid, then closes it when the amount is reached. System requires Dura's specially tuned relief valve kit to function. Can be ordered as a complete kit that includes the meter, valve and relief valve.

Auto-Batch™ Features

- Controls carrier flow using a 12-volt DC electric ball valve
- · Easily select manual or automatic operation
- Returns to last volume amount dispensed for easy repeatable batching
- Displays message when batch is completed
- Banjo® EVX® 2" or 3" Valves available for tank bypass system

2" & 3" High-Flow Dura-Meter™

- Intuitive menu-driven backlit display
- · Works with non-conductive materials
- · Ability to save up to five manual calibrations
- Option to display batch volume, total volume, and flow rate
- Volume measured can be displayed in Liters or Gallons
- Ability to calibrate allows for industry minimum straight line before/after meter*
- *See best practices document at duraproducts.com



2" AND 3" DURA **AUTO-BATCH**™ HIGH-FLOW METER

Fast. Simple. Safe.™

| ORDERING INFORMATION | | | |
|-------------------------|--------------------------|--------------------|--|
| 2" DPAB-HFM2V Viton® | | DPAB-HFM2E EPDM | |
| 3″ | DPAB-HFM3V Viton® | DPAB-HFM3E EPDM | |



| ORDERING INFORMATION | | | |
|-----------------------|------------|---|--|
| PRODUCT # DESCRIPTION | | | |
| 2" | MEVX220-DP | 2" Full Port Banjo EVX® Valve with Connector | |
| 3″ | MEVX300-DP | 3" Full Port Banjo EVX® Valve with Connector | |



| ORDERING INFORMATION | | |
|-----------------------|--------------|---------------------------------|
| PRODUCT # DESCRIPTION | | |
| 2″ | DPAB-HFM2PRV | 2" Relief Valve Plumbing Kit |
| 3" | DPAB-HFM3PRV | 3" Relief Valve Plumbing Kit |

| RELIEF VALVE KIT CONTAINS | | |
|---------------------------|--|--|
| Valve | Pressure Relief* | |
| Other | All hose clamps, gaskets, reducer couplings, and tees. | |

^{*} Custom pressure relief valve

| COMPARISON | | | |
|-----------------------------------|------------------|------------------|--|
| Specifications | 2" | 3″ | |
| Nominal Size | 2" | 3" | |
| Model | DPAB-HFM2 | DPAB-HFM3 | |
| Connection | M220 flange | M300 flange | |
| Meter Accuracy | +/- 0.5%* | +/- 0.5%* | |
| Fluid Flow Initiates Measurement | Yes | Yes | |
| Battery Size/Voltage | (2) 9 Volt | (2) 9 Volt | |
| Battery Life Indicator | Yes | Yes | |
| Backlit Display | Yes | Yes | |
| Maximum Pressure | 150 PSI | 150 PSI | |
| Minimum GPM | 40 | 80 | |
| Maximum GPM | 300 | 700 | |
| Minimum Temp | + 32 °F | + 32 °F | |
| Maximum Temp | + 140 °F | + 140 °F | |
| Meter Type/Style | Paddlewheel | Paddlewheel | |
| Body Construction Material | GF Polypropylene | GF Polypropylene | |
| Paddle Wheel Bearing | Sapphire | Sapphire | |

^{*} With manual calibration





