



DURA PRODUCTS



**FASTBATCH**  
VENTURI

Fast. Simple. Safe.™

**Reduce fill times by up to 50%!\***



### Speed, Simplicity and Safety in a Compact Design

Transform the way you mix and spray with the FastBatch Venturi, an automated venturi suction solution for efficient, accurate, and safe mixing.

### Fast: Speed and Productivity

**Efficient Operation:** Spend more time spraying and less time waiting with this all in one solution.

### Simple: Familiar and Reliable

**User-Friendly Design:** Built with trusted, high-quality, durable, familiar components and a straightforward operation, making it easy for anyone to use.

### Safe: Protecting Your Crops, Team and Equipment

**Precise Accuracy:** Every batch is mixed to perfection, ensuring consistent results for your crops.

**Operator Safety:** Designed with worker protection in mind, reducing exposure risks during operation.

### Compact Design: Big Performance, Small Space

**Space-Saving Footprint:** Requires no more space than a traditional mixing cone, making it an ideal fit for any operation.

Now with reconfigurable frame, Auto-Batch™ High-Flow Carrier System with **Bluetooth®** wireless connectivity and rinse with Dura manual valves.

ORDERING INFORMATION	
PRODUCT #	DESCRIPTION
DPFB-VENT2V2-12	2" 12VDC 2-Input Fastbatch Venturi System Viton® No Pump
DPFB-VENT3V2-12	3" 12VDC 2-Input Fastbatch Venturi System Viton® No Pump
DPFB-VENT2V4-12	2" 12VDC 4-Input Fastbatch Venturi System Viton® No Pump
DPFB-VENT3V4-12	3" 12VDC 4-Input Fastbatch Venturi System Viton® No Pump

PART NUMBER TAXONOMY INFORMATION		
DPFB-VENT3V4-12	DIGIT OPTION	DESCRIPTION
DPFB-VENTX	2	2" Plumbing
	3	3" Plumbing
DPFB-VENT3X	V	Viton®
	E	EPDM
DPFB-VENT3VX	2	2 input version
	4	4 input version
DPFB-VENT3V4-XX	12	12 volt DC
DPFB-VENT3V4-12-XX	Add TP at end	Transfer Input with Honda® Engine and Silicon Carbide seal
	Add WSTP at end	John Blue® Transfer Input with Honda® Engine and Wet Seal

\* Based on standard cone/venturi systems with 4 bulk inputs taking 20 minutes (VOC) vs 10 minutes for the FastBatch Venturi

Dura recommends the NOCO® GenPro 10X1 charger to connect a 12V battery system for static 110V installation/operation.



Dry Poppet Calibration Connnections



Dura 1" Electric Valves



Reusable magnetic labels for chemical identification on meter mount



40 Gallon Cone with chem knife and rinse



Auto-Batch™ High-Flow Carrier System with  
Bluetooth® wireless connectivity

SPECIFICATIONS	
SPECIFICATIONS	
<b>Main Plumbing Size</b>	2" or 3"
<b>Meters</b>	Auto-Batch™ High-Flow & Auto-Batch™ Meters
<b>Voltage</b>	12 Volt DC
<b>Connections</b>	M100-M220-M300 Flanges
<b>EV Open/Closed Indicator</b>	Yes
<b>Wiring</b>	On/Off 3 Wire
<b>Connector</b>	4 Pin Deutsch
<b>Calibration Connection</b>	Dry Poppets
<b>Cone</b>	40 gallon w/chem knife & rinse set up
<b>Maximum Pressure</b>	150 PSI
<b>Storage Temp</b>	-40° to 185° F (-40° C to 85° C)
<b>Operating Temp</b>	32° to 158° F (0° C to 70° C)
<b>Wetted Materials</b>	Glass Filled Polypropylene, 304 & 316 Stainless Steel, PTFE & Carbon Graphite filled PTFE, EPDM, Viton™, Ryton™, Santoprene, PVDF Kynar™
<b>System Dimensions</b>	58" L x 35" W



**DURA PRODUCTS**

Technology with Lasting Value

[www.DuraProducts.com](http://www.DuraProducts.com)

Arcadia, IN 46030 | (317) 984-4003