

6-N-1 System

DURA PRODUCTS

Technology with Lasting Value

DURA-PUMPTM **EASY CADDY**

High flow Dura-Pump™ pumping system can be used 6 ways with 3 mounting options. Quickly mount this pumping system on top of tank or top of 55 gallon drum, on side of tank or off the ground depending on user preference. Conversion Kits are available to mount system on Monsanto and Snyder type tanks.

/ Includes 2 Year Warranty

Pumping system includes:

/1" x 12ft EPDM discharge hose

/1" x 5ft EPDM suction hose

/2" Cam-lock with hose barbs and clamps

/ Ball valve nozzle

/ Dura-MeterTM (optional)

WITH Meter	WITHOUT Meter
DPEM-4312 12 volt	DPE-4012 12 volt
DPEM-4315 110 volt	DPE-4015 110 volt

(Available in EPDM, Viton*, or Silicone)

Must specify EPDM (product # and E), Viton* (product # and V), or Silicone (product # and S) when ordering.

Tanks/Totes/Drums sold separately.

SIDE MOUNT
Fasy Caddy secured on side of tote

The Easy Caddy system is our **top selling** and the industry's **most versatile** chemical transfer system



Call 855-502-3827 or Visit www.DuraProducts.com to Find Your Local Dealer

DURA-METERTM



DURA-METERTM

/ Made of impact resistant Lexan™ faceplate

/ 100% moisture-sealed circuitry

/ Menu driven backlit display

/ Plumbed both for in-line and 90 degree applications

/ Includes 2 Year Warranty

DP-3000E EPDM

DP-3000V Viton®

DP-3000S Silicone

Must specify EPDM (product # and E), Viton* (product # and V), or Silicone (product # and S) when ordering.



Customer should always

check calibration before use

Specifications	
Operating Temp	-10°F to 130°F, -23°C to 54°C
Flow Rate	2 to 22GPM, 7.5 to 83LPM
Meter Accuracy	+ /5%
Backlit Display	Yes
Maximum Pressure	40 PSI
	Polypropylene;
Wetted Materials	304 Stainless Steel; Ryton;
	EPDM, Viton®, or Silicone seals

Special Features

/ Extended battery life with use of 4 "AAA" batteries / Faceplate over-molded with Santoprene and filled with gel for improved shock resistance

