

# DURA-PUMP™ EASY CADDY

High-flow Dura-Pump™ pumping system can be used 6 ways with 3 mounting options. Quickly mount this pumping system on top of a tank or on top of a 30/55-Gallon Drum, on the side of tank, or off the ground depending on user preference. Conversion Kits are available to mount a system on Monsanto and Snyder type tanks.

Pumping system includes:

- / 1" x 12ft EPDM discharge hose
- / 1" x 5ft EPDM suction hose
- / 2" Camlock with hose barbs and clamps
- / Ball valve nozzle
- / Includes a 2-year Warranty & Maintenance Program
- / Dura-Meter™ (optional)



**SIDE MOUNT**  
Easy Caddy secured  
on side of tote

WITH Meter	WITHOUT Meter
DPEM-4312 12 Volt	DPE-4012 12 Volt
DPEM-4315 110 Volt	DPE-4015 110 Volt

Must specify EPDM (product # and E),  
Viton® (product # and V), or Silicone  
(product # and S) when ordering.

Tanks, Totes and Drums sold separately.

## 6-N-1 System

The Easy Caddy system is our **top selling** and the industry's **most versatile** chemical transfer system.



**TOP MOUNT**  
Easy Caddy secured  
on top of tote



**GROUND**  
Easy Caddy used  
from the ground



**DRUM**  
Easy Caddy used on  
a 30/55-Gallon Drum



**SNYDER TANK**  
Easy Caddy to a GEM Cap



**MONSANTO TANK**  
Easy Caddy to a MTS



**DURA PRODUCTS**  
Technology with Lasting Value  
[www.DuraProducts.com](http://www.DuraProducts.com)  
Arcadia, IN 46030 | (855) 502-3872





# DURA-METER™

- / Made of impact resistant Lexan™ faceplate
- / 100% moisture-sealed circuitry
- / Menu driven backlit display
- / Plumbed both for in-line and 90-degree applications
- / Includes a 2-year Warranty & Maintenance Program

DP-3000E EPDM

DP-3000V Viton®

DP-3000S Silicone

Must specify EPDM (**product # and E**), Viton® (**product # and V**), or Silicone (**product # and S**) when ordering.

## Specifications


Operating Temp	-10°F to 130°F, -23°C to 54°C
Flow Rate	2 to 22GPM, 7.5 to 83LPM
Meter Accuracy	+ / - .5%
Backlit Display	Yes
Maximum Pressure	40 PSI
Wetted Materials	Polypropylene; 304 Stainless Steel; Rytan; EPDM, Viton® or Silicone seals

## Special Features

- / Extended battery life with use of 4 "AAA" batteries
- / Faceplate over-molded with Santoprene and filled with gel for improved shock resistance



Customer should always  
check calibration before use



**DURA PRODUCTS**

Technology with Lasting Value

[www.DuraProducts.com](http://www.DuraProducts.com)

Arcadia, IN 46030 | (855) 502-3872

Call (855) 502-3872 or Visit [www.DuraProducts.com](http://www.DuraProducts.com) to Locate a Distributor.